

IP Attic Base IPATTC208



Designed to
surround
column shaft of
8" (20.32cm)
sitting on substrate

Torus
Diameter
call

Hole 8-1/8" (20.6cm)



Plinth 11-1/4" x 11-1/4" (28.6cm)

Materials

ArchPolymer™

an artificial wood primed white easy to install with the approved adhesive and a brad nailer. Finish joining edges with poly spackling compound. Optional Class A fire rating available. Exterior & Interior use

GRG-NeoPlaster™

Much stronger than traditional plaster Class A fire rated product. Screw & glue into place. Priming by others. Interior use.

GFRC-Zement™

A heavy concrete based composite
Class A Fire Rated - Interior & Exterior Use

Height
4-1/2"
11.4cm

Ovolo
Height
call

Plinth
Height
call

* All specifications subject to change without notice, E&OE

Final products & Measurements may vary from this brochure Manufacturing tolerances +- 1/8" (.31cm)



Imperial Productions®

Imperial Productions & Distribution Inc.

email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved

1-800-399-7585

+1-416-264-6096

DEC-25



Custom Request (Download & Fill-in)

email to sales@imperialproductions.com IPATTC208

Name _____

Date: _____

Contact: _____

Phone # _____

Email: _____

Address _____ ZIP/PC _____

MATERIAL SELECTION

ArchPolymer™ High Density Polyurethane, Primed ready to paint by Others (Interior/Exterior)

of Unit _____ for Residential

of FireRated Units _____ for Commercial Interior

GRG-NeoPlaster™ A new age plaster, Class A fire rated (Interior)

of Units _____

GFRC-Zeament™ A Concrete Composite (Exterior)

of Units _____

VALUE ADDED FINISHES

Factory Paint Color Code _____ Finish _____

Metal Coated: Type: _____

* Possible Limitations due to Quantity Requested and/or Application



Imperial Productions®

Imperial Productions & Distribution Inc.

email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved

1-800-399-7585 +1-416-264-6096