Attic Base
IPATTC210

Designed to surround column shaft of 10” (25.4cm) sitting on substrate

Materials

ArchPolymer™
an artificial wood primed white easy to install with the approved adhesive and a brad nailer. Finish joining edges with poly spackling compound. Optional Class A fire rating available. Exterior & Interior use

GRG-NeoPlaster™
Much stronger than tradiitonal plaster Class A fire rated product. Screw & glue into place. Priming by others. Interior use.

GFRC-Zeament™
A heavy concrete based composite
Class A Fire Rated - Interior & Exterior Use

Hole 10-1/4” (26cm)

Torus Diameter 14” 35.5cm

Height 8” 20.32cm

Torus Height 5-1/2” 13.9cm

Plinth Height 3” 7.6cm

Plinth 15-1/2” x 15-1/2” (39.37cm)

* All specifications subject to change without notice, E&OE
Final products & Measurements may vary from this brochure Manufacturing tolerences +- 1/8” (.31cm)

Imperial Productions® 1-800-399-7585 +1-416-264-6096
Imperial Productions & Distribution Inc.
email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved

JAN-25

Custom Request (Download & Fill-in)

emailto sales@imperialproductions.com IPATTC210

Name _____ Date:_____

Contact: _____

Phone # _____

Email: _____

Address _____

_____ZIP/PC _____

MATERIAL SELECTION

ArchPolymer™ High Densiity Polyurethane, Primed ready to paint by Others (Interior/Exterior)
# of Unit _____ for Residential
# of FireRated Units _____ for Commercial Interior

GRG-NeoPlaster™ A new age plaster, Class A fire rated (Interior)
# of Units _____

GFRC-Zeament™ A Concrete Composite (Exterior)
# of Units _____

VALUE ADDED FINISHES

Factory Paint Color Code_____ Finish _____

Metal Coated: Type: _____

* Possible Limitations due to Quantity Requested and/or Application

Imperial Productions® 1-800-399-7585 +1-416-264-6096
Imperial Productions & Distribution Inc.
email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved