Attic Base
IPATTC211

Designed to have ArchPolymer™ Shaft sitting on the Flat of 12-1/2”

Materials

ArchPolymer™
an artificial wood primed white easy to install with the approved adhesive and a brad nailer. Finish joining edges with poly spackling compound. Optional Class A fire rating available. Exterior & Interior use

GRG-NeoPlaster™
Much stronger than tradiitonal plaster Class A fire rated product. Screw & glue into place. Priming by others. Interior use.

Zeament™
A heavy concrete based composite
Class A Fire Rated - Interior & Exterior Use

Hole 12-1/4” (31cm)

Total Height
10” (25.4cm)

Torus Height
7” (17.78cm)

Plinth Height
3” (7.62cm)

Plinth 17-1/2” x 17-1/2” (39.37cm)

* All specifications subject to change without notice, E&OE
Final products & Measurements may vary from this brochure Manufacturing tolerences +- 1/8” (.31cm)

Imperial Productions® 1-800-399-7585 +1-416-264-6096
Imperial Productions & Distribution Inc.
email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved

JAN-24

Custom Request (Download & Fill-in)

emailto sales@imperialproductions.com IPATTC211

Name _____ Date:_____

Contact: _____

Phone # _____

Email: _____

Address _____

_____ZIP/PC _____

MATERIAL SELECTION

ArchPolymer™ High Densiity Polyurethane, Primed ready to paint by Others (Interior/Exterior)
# of Unit _____ for Residential
# of FireRated Units _____ for Commercial Interior

GRG-NeoPlaster™ A new age plaster, Class A fire rated (Interior)
# of Units _____

GFRC-Zeament™ A Concrete Composite (Exterior)
# of Units _____

VALUE ADDED FINISHES

Factory Paint Color Code_____ Finish _____

Metal Coated: Type: _____

* Possible Limitations due to Quantity Requested and/or Application

Imperial Productions® 1-800-399-7585
Imperial Productions & Distribution Inc.
email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved