



Attic Base IPATTC211



Designed to have
ArchPolymer™
Shaft sitting on the
Flat of 12-1/2"

Materials

ArchPolymer™

an artificial wood primed white easy to install with the approved adhesive and a brad nailer. Finish joining edges with poly spackling compound. Optional Class A fire rating available. Exterior & Interior use

GRG-NeoPlaster™

Much stronger than tradiitonal plaster Class A fire rated product. Screw & glue into place. Priming by others. Interior use.

Zeament™

A heavy concrete based composite
Class A Fire Rated - Interior & Exterior Use

Hole 10-1/2" (26.7cm)

Flat
12-1/2"
31.75cm

Height
9-1/2"
24cm



Plinth 18-1/2" x 18-1/2" (47 x 47cm)

* All specifications subject to change without notice,
Final products & Measurements may vary from this brochure Manufacturing tolerences +/- 1/8" (.31cm)



Imperial Productions®

1-800-399-7585

Imperial Productions & Distribution Inc.

email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved

JAN-24



Custom Request (Download & Fill-in)

emailto sales@imperialproductions.com

IPATTC211

Name _____

Date: _____


Contact: _____

Phone # _____

Email: _____

Address _____

ZIP/PC _____



MATERIAL SELECTION

ArchPolymer™ High Density Polyurethane, Primed ready to paint by Others (Interior/Exterior)

of Unit _____ for Residential

of FireRated Units _____ for Commercial Interior

GRG-NeoPlaster™ A new age plaster, Class A fire rated (Interior)

of Units _____

GFRC-Zeament™ A Concrete Composite (Exterior)

of Units _____

VALUE ADDED FINISHES

Factory Paint Color Code _____ Finish _____

Metal Coated: Type: _____

* Possible Limitations due to Quantity Requested and/or Application



Imperial Productions®

1-800-399-7585

Imperial Productions & Distribution Inc.

email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved