Tuscan Smooth Square IPTUSQ0914S-TCTB

Fiberglass

<= C1 =>Shaft (A) 13-1/2" x 13-1/2" C2 =>34.29 x 34.29cm Capital Width & Depth (C1) 19-1/4" x 19-1/4" (48.89 x 48.89cm) Capital Height (C2) 4-3/4" (12cm) **Total** Height 9 Feet Base Width & Depth (B1) 2.74 meters 19-3/8" x 19-3/8" (49.2 x 49.2cm) <= A => Base Height (B2) 7-3/4" (19.68cm) Weight 57 lb (25.8 kg) Load Bearing to 10,000 (4.53 metric tons) Load must be distributed evenly over the shaft Minimum Inside 12" x 12" (30.48cm x 30.48cm) Priming & Painting by others B2 =>Optional Split for Post Wrap <= B1 =>Pilaster Engaged Outside Wall Inside

* Assembly required, drawing not to scale, final measurements may vary due to manufacturing tolerences E&OE

Wrap

* For Load Bearing Application, consult with your structural engineer for suitability in your local area sold as unfinished building components - integration hardware by others * All specifications subject to change without notice

Corner

Corner

Request for Quote IPTUSQ0914S Download and Auto Fill PDF

Name / Company	
Phone Email _	
Billing Address	
City	State / Prov
ZIP / PCode	
Ship to Address	
City	State / Prov
ZIP / PCode	_
Quantity Whole	
Split Post Wrap Split for Pilaster	
Split for Engaged Split	Wall Wrap
Split Outside Corner Split Inside Corner	
Note:	