

Projection: 1" (2.54cm)

Available Materials

ArchPolymertm

an artificial wood primed white easy to install with the approved adhesive and a brad nailer. Finish joining edges with poly spackling compound.

Optional Class A fire rating available Exterior & Interior use

GRG-NeoPlaster_{TM}

Much stronger than tradiitonal plaster Class A fire rated product Screw & glue into place Priming by others Interior use

FlexibleResinMold®

A Flexible synaptic polymer for Interior & Exterior Use

Apply to Walls / Doors / Ceilings Mirrored walls and stand alone mirrors





Ships World Wide

* All specifications subject to change without notice, Final products & Measurements may vary from this brochure



Custom Request (Download & Fill-in) emailto sales@imperialproductions.com IPNP4145


Name	Date:
Contact:	
Phone #	
Email:	
Address	
	7IP/PC
MATERIAL SELECTION	
ArchPolymertm A synthetic Plaste # of Feet # of FireRated Feet	er, White Primed Ready to Paint (Interior/Exterior) for Residential for Commercial Interior
GRG-NeoPlasterTM A new age p	-
Flexible ResinMold® vaults, of Feet	Class A fire rated (Interior/Exterior) Restriction on Radius
GFRC-ZeamentTM A Composite # of Feet	e of Portland Cement, Class A fire rated (Interior)
VALUE ADDED FINISHES Factory Paint Color Code_	
Metal Coated: Type:	

^{*} Possible Limitations due to Quantity Requested and/or Application



Profile: IPNP4145 Flexible ResinMold®

1) ARCH - True 1/2 Circle & Eyebrow **Elevation Drawing**






Please Provide Inside Crown Measurements

D= Distance to Side from C _____ Number of Arches: ____

2) CIRCLE

Diameter A



or Circumference

of Circles _____



3) CURVED WALL Plan View Drawings

Convex Wall	 A = Depth=	

Length of Curve

Concave Wall	A = Depth=

Length of Curve

4) STRAIGHT LENGTHS

Total Feet (Meters) Required: _____